
Square Aluminum Light Poles



Specifications

Pole Shaft: The shaft is constructed from high-strength seamless 6061-T6 aluminum tubing. It is available with side drilling for arm-mounted area lighting luminaires or with tenon mounts for floodlights and post-top luminaires. The shaft conforms to ASTM F1554 Grade 55 requirements.

Finish: The poles feature a textured architectural powder-coat finish in bronze, black, or white. The baked finish ensures maximum paint adhesion, durability, and long-term resistance to wear.

Hand Hole: Each pole is equipped with a cast-iron reinforced hand hole with a grounding provision located 1'-6" above the base. The hand hole assembly includes a secure cover with attachment hardware, designed to facilitate safe electrical connections and routine maintenance.


Surface Treatment: The poles are hot-dip galvanized to provide superior corrosion resistance and a long-lasting protective coating.


Accessories Included: Each pole is furnished with a base cover, a screw positioning plate, anchor bolts, and all required mounting hardware.


Optional Accessories: Available top configurations include a Tenon Top, a Top Cap Only, or an Open Top. These options are designed to accommodate standard slip-fit dimensions.


Design Criteria: The published EPA and weight ratings are based on commercial design criteria with a 1.3-second gust factor. The standard configuration includes a 2. 5-inch top adapter, and the pole is manufactured with side openings to accommodate arm-mounted installations. If the top adapter is not required, it can be removed and the pole sealed with a removable top cap.


Square Aluminum Light Poles













| CATALOG | HEIGHT | GAUGE | SIZE | BASE | BOLT Circle | BOLT Size | WEIGHT (LBS) | EPA 80 | EPA 90 | EPA 100 | EPA 110 | EPA 120 |
|-----------------|--------|-------|-------|------|----------------|---------------------|-----------------|-----------|-----------|------------|------------|------------|
| JCL-SAL10FT4-8G | 10ft | 8 | 4"x4" | 11" | 8.27"-11.42" | M0.79"x19.69"x3.94" | 41 | 13.5 | 11.3 | 8.9 | 7.3 | 6.8 |
| JCL-SAL15FT4-8G | 15ft | 8 | | | | | 55 | 7.3 | 5.1 | 4.4 | 3.8 | 2.9 |
| JCL-SAL20FT4-8G | 20ft | 8 | | | | | 88 | 3.2 | 2.6 | 1.5 | 0.9 | 0.3 |
| JCL-SAL25FT4-3G | 25ft | 3 | | | | | 132 | 8.3 | 6.2 | 5.2 | 4.2 | 3.6 |
| JCL-SAL30FT5-3G | 30ft | 3 | 5"x5" | | 9.86"-11.42" | M0.95"x36"x4" | 198 | 10.1 | 7.0 | 5.7 | 3.7 | 2.4 |



Square Aluminum Light Poles

ORDERING INFORMATION

EXAMPLE: JCL-SAL10FT4-8G-DB-TT



INSTALLATION

